



SNAIGĖ STANDARD line PHARMACEUTICAL REFRIGERATORS ENSURING OPTIMAL MEDICATION STORAGE

Comply with DIN 13277

STANDARD line refrigerators have all the essential features and performance functions required to meet the performance criteria of the DIN 13277 standard. This standard provides the requirements and test specifications for medical and laboratory refrigerators and freezers.

Test method EN 60068-3

SNAIGĖ medical refrigerators are tested according to EN 60068-3 in order to ensure the stability and constancy of the internal temperature. The test method involves measuring the temperature at 15 different points inside the refrigerator.

Ecological and environmentally friendly

STANDARD line refrigerators are manufactured using only non-harmful, non-ozone-depleting and non-greenhouse-effect refrigerating and insulating materials. Natural resource-saving materials and electricity from renewable energy sources are used in the refrigerator manufacturing process.

MD14DC-P3B1QX2 / MD14DC-P6B1QX2

STANDARD line Pharmacy refrigerator



MD14DC-P6B1QX2

MD14DC-P3B1QX2

KEY FEATURES



Electronic control system

An electronic controller installed in the STANDARD line refrigerators provides continuous monitoring of the temperature inside the refrigerator.



Temperature stability

The refrigerator is designed to maintain maximum stable temperature and minimal fluctuations. The maximum possible temperature change within the entire internal space of the refrigerator is only ± 1.8 °C. Thus, the internal microclimate is maintained, creating suitable conditions for the storage of medications and medicines.



Cooling system with circulating air

The SNAIGĖ smart fan for medical refrigerators operates very efficiently. It turns off as soon as the refrigerator door is opened, so the air circulation in the refrigerator stops. Once the door is closed, the fan starts again and the air circulation is resumed. This fan operation prevents rapid temperature changes and helps to maintain a stable temperature inside the refrigerator, contributing to the preservation of medicines and medications.



Protection against contact with cold surfaces

The evaporator of the refrigerator has a special cover so that medications and medicines do not have direct contact with the evaporator and do not get cold. In addition, this protection against contact with cold surfaces increases the temperature stability.



KEY FEATURES



Warning temperature alarm

In order to ensure the maximum safety of stored medicines and medications, the integrated warning temperature alarm sends a warning signal with sound and image when a certain temperature value exceeds or falls below the set limit.



Access to an additional external sensor

An additional external sensor can be attached if required for additional control of the temperature of medication storage in the refrigerator. SNAIGÉ medical refrigerators are equipped with a 12.5 mm diameter access for an additional external sensor, which helps avoid any negative effect of the cables of the external sensor on the sealing strip of the door, the tightness of the refrigerator and the risk to the personnel caused by the cables of the sensor.




LED lighting

The horizontal LED strip perfectly illuminates the entire inside of the refrigerator. Clear visibility on all shelves makes it easy to find the necessary medications. Moreover, the interior lighting of SNAIGÉ medical refrigerators is not just efficient – it's also smart: the light turns on only when the door of the refrigerator is opened. This way, medications are protected from excess light, and most importantly, energy costs are reduced.



Self-closing door

The door of the SNAIGÉ medical refrigerator closes automatically, without any risk of the door bouncing. This ensures convenience and safety for medical personnel in their daily use of the refrigerator, and also completely eliminates the risk of the refrigerator door being accidentally left open. The self-closing door contributes to maintaining a stable temperature, as well as supporting the integrity of stored medicines and medications.



Changeable direction of the door opening

SNAIGÉ medical refrigerators are manufactured with door hinges on the right side, although the door opening direction can be easily changed. This can be done independently, as the change does not require additional materials or repair service.

Replaceable door sealing strip

The door sealing strip can be easily replaced independently without additional materials or a repair service.



Commitment to Quality

Every single unit produced goes through multiple quality checks at every stage of the production process. Furthermore, prior to packing of the finished unit, each one is subjected to full operational performance checks ensuring that the electric system, cooling system and general operation of the unit is within our own tight specifications. All testing is conducted in a designated, semi-automated testing area so we can be absolutely certain that every one of our units meets our customers Safety and Operational expectations. No one SNAIGÉ appliance leaves our plant without being fully checked.

TECHNICAL DATA

Pharmacy refrigerator	MD14DC-P3B1QX2	MD14DC-P6B1QX2
EAN code	4770104014079	4770104014086
Gross capacity, l	130	
Net capacity, l	100	
Factory temperature setting, °C	+5	
Fluctuation, °C	0,5	
Gradient, °C	2,9	1,8
Average temperature limits of products (min / max), °C	From +2 to +8	
Increase in temperature from +5 °C to +10 °C (empty, +25 °C TU)	40 min.	
Decrease in temperature from +25 °C to +5 °C (empty, +25 °C TU)	40 min.	
Ambient temperature range, °C	from +10 to +35	
Airborne acoustical noise emissions, dB(A) re1 pW	42	
Refrigerant	R600a	
Daily consumption, kWh/24h	0,751	0,482
Annual energy consumption, kWh/year	274	176
Rated voltage, V	220 - 240	
Rated frequency, Hz	50	
Access port	Yes	
Cooling system	Fan forced cooling	
Defrost	Automatic	
Volt-free alarm contact	No	
Interior light	Ceiling LED light strip	
Number of shelves	2 adjustable +2 bottoms	
Shelf size (W x D), mm	420 x 324, bottoms 465 x 263 and 445 x 180	
Maximum load per shelf, kg	20	
Shelf material	Wire shelves coated by white polymer paint	
Side wall material	Steel, white painted	
Inner cabinet material	HIPS polystyrene	
Type of door	Double panel selective glass in aluminum profile	Full-panel door, white painted
Reversible door	Yes	
Self closing door	Yes	
Type of lock	Mechanical	
Adjustable foot at the front	2	
Foot behind	2	
External dimensions (H x W x D), mm	870 x 560 x 620	
Internal dimensions (H x W x D), mm	725 x 465 x 392	
Package dimensions (H x W x D), mm	1080 x 580 x 650	
Weight net, kg	37	
Weight gross, kg	48	

Contact us:

LabTeam Scandinavia AB [LabTeamet]

www.labteamet.com

order@labteamet.com

Tel: +46 423009130 / +45 36 980230

